

APPENDIX 5 (c)
2022 SCOTTISH CITROEN C1 CUP
TECHNICAL REGULATIONS

5.1 INTRODUCTION

- 5.1.1 The following Technical Regulations are set out in accordance with the Motorsport UK specified format and it should be clearly understood that if the following texts do not clearly specify that you can do it you should work on the principle that you cannot.
- 5.1.2 Anything that is not explicitly authorised in writing by the Championship Organisers and anything that is not specified either in these regulations or in any Official Championship Bulletin is therefore strictly forbidden and thus will be regarded as a breach of these Technical Regulations and may be penalised as described in Section 4.
- 5.1.3 It should be clearly understood that Technical Regulations will be strictly enforced and any modification, for the purposes of these regulations, defined as, any change in the design, material, shape, dimension and / or surface finish of any component except for basic manufacturing processes, normal wear and published service or repair procedures, modification, addition, variation, tuning or removal other than specifically permitted in these regulations is prohibited.

5.2 GENERAL DESCRIPTION

- 5.2.1 The following regulations are for competitors participating in standard production pre 30 April 2014 Citroen C1 998cc 3 door saloon vehicles. The class was conceived as a low-cost form of motorsport. It is intended as a racing formula for the continued use and enjoyment of the C1 where driving skills and car control are of paramount importance and where technical development is strictly prohibited.
- 5.2.2 **Examination of Vehicles**
The Licenced Eligibility Scrutineer / Championship Organisers reserve the right to inspect, test, measure, seal or impound any component fitted to or used in conjunction with any car registered in the Championship either personally or through a nominated representative. The costs of such checking shall be borne by the Championship Organisers, but the Championship Organisers shall not be liable for the costs of stripping or reassembly of vehicles after the checks have been carried out. This will be the sole responsibility of the Competitor. Exceptions to this may include appeal / protest according to the current Motorsport UK Yearbook. Any breach of the Technical Regulations or a breach of the procedure surrounding the Technical Regulations will be the subject of a report to the Clerk of the Course.
- Any component sealed by a Motorsport UK Licensed Scrutineer must remain sealed and may not be tampered with in any way. In the event of a seal needing to be broken for repair or replacement, prior to doing so the Championship Eligibility Scrutineer must be informed in writing and approve the seal being broken. Re-sealing by a Motorsport UK Licenced Scrutineer will take place after technical checks have been made at the next race meeting.

If a vehicle/component is sealed for subsequent technical examination the Championship Eligibility Scrutineer, within the applicable time limit, will state to the Competitor/ Championship Organisers that he will examine the vehicle/component on a stated date and time and at a specified location and the sealed items must be made available for his inspection. These arrangements are not negotiable. If a vehicle/component is not made available for an eligibility examination as required by the Championship Eligibility Scrutineer, it will be considered as ineligible and will be reported as such to the Clerk of the Course for the application of penalties laid down under Motorsport UK Regulations and these Championship Regulations.

5.3 SAFETY REQUIREMENTS

- 5.3.1 Motorsport UK Appendix K Safety Criteria Regulations will apply as relevant, in particular K1, K1.2.1, K1.3.1 - 4, K5, K6, K8, K9, K10, K13 & K14.
- 5.3.2 A plumbed in fire extinguisher that complies with Motorsport UK Regulations is mandatory (Q13.10.7.) (4 litre minimum recommended.) The driver's activation pull cable or button shall be mounted on the centre console. For 2022 fire extinguishers must be an FIA homologated standard Fire Extinguisher Systems in Competition Cars (1999) or FIA Standard 8865-2015 and be serviced by the manufacturer or their agent within the preceding 24 months.
- 5.3.3 For cars racing before January 1st 2017 a steel roll cage complying with the Motorsport UK Yearbook must be installed. The roll cage must be fitted with door bars to both sides of the car at hip level. For cars first raced after January 1st 2017 the roll cage must be a Safety Devices standard bolt in cage in one of the following 2 configurations:

Configuration 2

SD Part Number	Description
RBC052 3SXU	Front roll cage with windscreen reinforcement bar for unique single door bars, with roof cross diagonals.
RBC052 5XSU	Rear roll cage, single fixed diagonal for single door bars and roof cross.
RBC052 DSUN	Unique single door bar, near side (left hand side).
RBC052 DSUO	Unique single door bar, off side (right hand side).
RBC052 SB	Rear strut brace/harness mount.

Configuration 3

SD Part Number	Description
RBC052 3SXX	Front roll cage with windscreen reinforcement bar for cross door bars and roof cross.
RBC052 5SXX	Rear roll cage, cross diagonal, lower backstays, for roof cross and cross door bars.
RBC052 DXUN	Cross door bar, near side (left hand side).
RBC052 DXUO	Cross door bar, off side (right hand side).
RBC052 SB	Rear strut brace/harness mount.

Padding dangerous points of the roll-bar with Motorsport UK compliant padding is recommended in order to prevent injury.

- 5.3.4 Rear harness straps are to be mounted on a roll cage harness bar to conform to Motorsport UK and seat harness manufacturers regulations.
- 5.3.5 FIA homologated seat belts are mandatory (Q13.10.2). Particular attention should be given to seat belt angles and anchorage. See FIA 253-42.
- 5.3.6 It is mandatory to use a harness with a minimum of 5 fixing points, where at least one fixing point is designed to prevent the driver from sliding forward and under the lap straps. Harnesses must be suitable for use with a Frontal Head Restraint (FHR) device and be properly installed in the car in accordance with the manufacturer's installation instructions. Installation guidance can also be found in the FIA publication 'Guide for the use of HANS® in international motor sport'.

5.4 GENERAL TECHNICAL REQUIREMENTS & EXCEPTIONS

The following Technical Regulations are set out in accordance with the Motorsport UK specified format and it should be clearly understood that if the following texts do not clearly specify that a modification can be made to the car, then that modification is not permitted. The fact that some modifications are mentioned as prohibited does not imply that others are allowed. If any doubt exists about the legality or acceptability of any modification, then please request clarification from the Eligibility Scrutineer or the Championship Organisers **prior** to any work being undertaken.

5.4.1 Definition of terms:

- 5.4.1.1 **STANDARD:** The word 'standard' used within these technical regulations as a description of components is to be interpreted as per 'Standard Part' defined in Section B – Nomenclature & definitions in the Motorsport UK Yearbook. Checking will be by comparison to spare parts supplied by the manufacturer's official agent, comparison to standard parts or by any other means necessary to ensure compliance.
Standard Part: *Is a part, the specification, features, location and method of operation of a part are as provided when new by the motor manufacturer for the model and date of car as shown on the entry form*
- 5.4.1.2 **STANDARD PATTERN:** The phrase 'standard pattern' used within these technical regulations as a description of components is to be interpreted as per 'Standard Pattern Part' defined in Section B – Nomenclature & definitions in the Motorsport UK Yearbook. Checking will be by comparison to standard pattern part or any other means necessary to ensure compliance.
Standard Pattern Part: *A replacement part that has a similar form shape and features as the standard part and is made using similar materials and manufacturing processes e.g. a standard part manufactured by a non-original equipment supplier that is fully interchangeable with the standard part.*
- 5.4.1.3 **COMPONENTS:** The phrase 'component' used within these technical regulations shall be considered to be ANY individual part or assembly of parts used in the construction of the vehicle.

- 5.4.2 The car must be of sound construction, in good mechanical condition and well maintained in accordance with Motorsport UK General Technical Regulations (Sections J & Q) as appropriate. It must be capable of passing an MOT inspection or equivalent for overseas registered cars. It must be presented in good order. All inspection areas e.g. engine, gearbox, suspension components, etc. must be in a clean condition.
- 5.4.3 The Championship Organisers reserve the right to require any competitor to remove any part, or assembly of parts, from the car to be compared and checked against a standard or pattern part or assembly of parts. The Championship Organisers will, where appropriate, supply a replacement permitted part or assembly of parts which must be used until the Organisers determine the legality of the parts that have been removed. Any non-compliance will be dealt with under normal Motorsport UK technical rules for infringement. Additional fines to those applied by Motorsport UK may be applied by the organisers for infringements. The competitor will be liable for all costs relating to the exchange parts.
- 5.4.4 The Championship Organisers reserve the right to exchange any part or assembly of parts on the car for standard ones at any time during a race meeting on any competing car.
- 5.4.5 Prior to competing in the 2022 Scottish C1 Cup the vehicle must undergo a Safety Scrutineering inspection which will be undertaken by the SMRC Chief Scrutineer, Championship Eligibility Scrutineer or their appointed deputies, unless the vehicle competed in the same condition in the 2021 Championship. Additionally all vehicles must undergo a Safety Scrutineering inspection at least every 4 events. Any vehicle involved in an accident, or having been modified in any way, should be represented to the Scrutineers for further examination (Motorsport UK General Regulation J.3.1.2). A record of inspections will be maintained by the Championship Organisers. Scrutineering self-declaration forms must be lodged with the Event Organisers a minimum of 3 days prior to every event. The Event Organisers may select cars for pre-event safety inspections, the method of selection and times/locations for inspection will be notified in the event SRs. This regulation forms part of the Motorsport UK approved Scrutineering trial and may be amended at any time.

5.5 CHASSIS:

- 5.5.1 A standard Citroen C1 3 door vehicle must be used. LHD or RHD is permitted.
- 5.5.2 No part of the monocoque shell shall be removed, modified or added to. For the avoidance of doubt this includes any welding to stiffen or otherwise modify the shell or any brackets or parts of brackets attached to the monocoque shell or bodywork panels except as specified in 5.5.3.
- 5.5.3 The tabs at the left and right ends of the steering column support bar that provide an M6 threaded fixing for the dash panel may be shortened to facilitate the fitting of the cage front legs.

5.6 BODYWORK:

5.6.1 General

- 5.6.1.1 It shall be the intention, at all times, to preserve a standard external appearance to the cars.
- 5.6.1.2 It is permitted to apply paint, decals, stickers or wraps to the car with the exception that the areas reserved for sponsorship are not covered.
- 5.6.1.3 All doors must be fitted with original lock fittings and operating mechanisms, and must be kept unlocked during any practice or competition. If the vehicle is fitted with central locking, the central locking fuse (Fuse F2 – second one down on RHS of instrument housing) must be removed. The rear hatch key operated release mechanism on a non-central locking car may be replaced by the push button mechanism from a central locking car.

5.6.2 Interior

- 5.6.2.1 No part of the interior which is an integral part of the monocoque shell may be removed, modified or added to except the drilling of 12 x 25mm holes in the sills to accommodate the welded roll cage feet.
- 5.6.2.2 The cups spot welded to the top of the suspension towers must be removed to accommodate the roll cage backstay feet.
- 5.6.2.3 The front bulkhead must comply with the requirements of the Motorsport UK Yearbook. Two holes may be drilled to allow the cable pulls to pass through. Two holes may be drilled to allow the battery to master switch cables to pass through. These 4 holes must be fitted with grommets and ensure the fire protection integrity of the bulkhead. A further hole may be drilled to accommodate the fire extinguisher pipe.
- 5.6.2.4 Interior trim, fittings, courtesy light and passenger seats may be removed except as specified below. The dashboard must remain fitted with the radio, all heater controls, lights and switches must remain fully operational as intended by the manufacturer. A close-fitting slot cut-out in the dashboard is permitted to facilitate the fitting of the roll cage. The centre console and handbrake surround must also be fitted.
- 5.6.2.5 The internal door trims may be replaced by panels supplied by the C1 Racing Club. If these are not used, the standard internal door trims must be fitted but may be modified to facilitate clearance around the roll cage door bars.
- 5.6.2.6 The standard driver's seat must be replaced with a racing seat approved to FIA 8855-1999 as a minimum and must be fitted in the manufacturers intended position using the original seat fixing points.
- 5.6.2.7 Adjustable seat rails may be fitted. They must comply with Motorsport UK regulation K.2.2.1.

- 5.6.2.8 It must be possible to refit the passenger seat without moving or removing anything other than the ballast tray.
- 5.6.2.9 The original pedal box with original pedals must be fitted in its original position, using the standard mountings. It is permissible to add extension plates to the pedals. The maximum size of the pedal extensions is 120mm high x 80mm wide x 4mm thick. These must be attached directly to the pedals. The use of spacers between the pedals and plates is prohibited.
- 5.6.2.10 An aluminium floor plate of maximum dimensions 650mm x 500mm x 3mm may be installed to the driver's side foot well. A foot rest may be fitted to this plate on the left-hand side. Ballast must not be fitted underneath this plate.
- 5.6.2.11 If a rev counter is not fitted as standard equipment, a standard Citroen C1, Peugeot 107 or Toyota Aygo rev counter may be fitted. For right hand drive cars the rev counter must be fitted on the right hand side of the main instrument binnacle, for left hand drive cars the rev counter must be fitted to the left hand side of the main instrument binnacle.
- 5.6.2.12 An electronic lap timer may be fitted. If fitted this shall get its power from either the cigarette lighter socket or from the master switch, no other power source is permitted. The fitting of any other additional instrumentation, data loggers, or switches and wiring is not permitted including battery powered or removable devices.
- 5.6.2.13 Ducts, no longer than 300mm and 75mm or less in diameter, may be fitted to the driver and passenger dashboard air vents to aid driver ventilation.
- 5.6.3 **Exterior**
- 5.6.3.1 No panel may be cut, drilled or in any other way modified other than those detailed in these regulations.
- 5.6.3.1.1 Driver/passenger door windows may be converted from manual to electric operation by the use of OEM parts only. Additional electrical wiring is permitted to enable the operation of the windows as appropriate.
- 5.6.3.2 3 rear view mirrors must be fitted as a minimum (1 interior and 2 exterior). A wide-angle interior mirror is recommended. External mirrors must all be standard unmodified C1 mirror assemblies fitted in the manufacturers intended position.
- 5.6.3.3 All mirrors must provide a view to the rear of the car and must not be adjusted to provide an aerodynamic advantage. Both door mirrors must provide a rear view, as intended by the manufacturer, at all times.
- 5.6.3.4 Transparent coloured film may be fitted to rear view mirrors to reduce glare. This must not reduce the effectiveness of the rear-view mirrors in daylight.

- 5.6.3.5 All elements of the standard front and rear bumper assemblies (including the crash bar(s)) must be fitted. The front bumper may have a slot cut into it on each side to facilitate the fitting of the optional spot lights detailed below in 5.10.2.2. It may also have a slot cut into it on each side to facilitate fitting wire tow straps under Motorsport UK General Regulation Q.13.1.3(b).
- 5.6.3.6 The bonnet must be secured by one of the following mechanisms:
- The standard bonnet catch with the primary latch disabled and 2 locking pins or straps conforming to Motorsport UK regulation Q.13.2.6.
 - 2 locking pins or straps conforming to Motorsport UK regulation Q.13.2.6.
- It is permissible to drill 2 holes through the bonnet and engine bay front cross member to install bonnet pins. It is permissible to drill a maximum of 4 holes of maximum diameter 6mm in the bonnet outer skin and 4 holes of maximum diameter 6mm in the bumper to install bonnet straps
- 5.6.3.7 It must be possible to open the rear boot glass lid without the use of a key from the outside of the vehicle. This may be achieved either by fitting the boot lid catch from a central locking car or by fitting a pull cable to the original key operated boot lid catch.
- 5.6.3.7.1 Opening method(s) must be indicated by an adjacent 'OPEN' decal or similar.
- 5.6.3.8 The windscreen must be of HPR laminated glass.
- 5.6.3.9 The standard toughened glass side and rear windows must be retained.
- 5.6.3.10 N/A
- 5.6.3.11 The standard window winding mechanism (electric or manual) must be retained and must be fully operational.
- 5.6.3.12 All body panels must be standard or standard pattern parts.
- 5.6.3.13 The mandatory lap timing transponder must be fitted to the front inner wing in the position shown:

See 5.10.1.2 for wiring regulations.



- 5.6.3.14 Extra fasteners and strengthening plates (maximum size 1mm thick x 30mm x 80mm) may be fitted, one plate to each side front and/or rear, to the outside of the junction between the front wings and the front bumper and/or the outside of the junction between the rear quarter and the rear bumper. Alternatively, front bumper to wing/rear quarter fastener attachment may be fitted using a washer/bobbin and fastener and elasticated coupler.
- 5.6.3.15 A mandatory guard supplied by the C1 Racing Club must be fitted to the underside of the floor pan to protect the brake and fuel pipes as they exit the engine bay.
- 5.6.3.16 The lower (metal) and upper (plastic) scuttle trays below the windscreen may be modified in the following ways:
- A hole (maximum diameter 32mm) may be drilled in the lower scuttle tray immediately above each front strut to allow an allen key to be inserted into the top of the strut shaft. The holes must have closed grommets fitted to maintain the fire protection of the scuttle tray.
 - Up to 3 holes may be drilled in the lower scuttle tray to allow pull cables to pass through. Sealing grommets must be fitted to these holes to maintain the fire protection of the scuttle tray.
 - Up to 3 holes may be made in the upper scuttle tray to allow pull cable handle fittings to be mounted. A reinforcing plate may be used on the underside of the scuttle tray to strengthen it. One pull cable must operate the bonnet catch, one to operate the fire extinguisher and one to operate the master cut-out switch. All handles must be marked with stickers on the bonnet.
 - Extra fasteners and a plastic plate (maximum dimensions 2.5mm x 30mm x 125mm) may be fitted over the joint between the left and right halves of the plastic scuttle tray.
- 5.6.3.17 Sound deadening materials may be removed from the engine bay and underside of the bonnet.
- 5.6.3.18 Front wheel arch liners may be removed. However, it is recommended that they remain in place to protect the auxiliary belt from stones.
- 5.6.3.19 Rear spoilers are not permitted.
- 5.6.3.20 Towing eyes must be fitted front & rear and must comply with Motorsport UK General Regulation Q.13.1.3.
- 5.6.4 **Silhouette**
- 5.6.4.1 The original silhouette must be maintained, except the variation caused by the fitment of the C1 Racing Club approved front driving lights (see 5.10.2.2) and/or the fitting of wire towing straps in accordance with Motorsport UK General Regulation Q.13.1.3(b).

5.6.5 Ground Clearance

- 5.6.5.1 Ground clearance must comply with the requirements of the Motorsport UK Yearbook. For the purposes of this regulation bottom front strut brace and exhaust are considered to be part of the car and are subject to the same ground clearance rules.

5.6.6 In-Race Repairs

- 5.6.6.1 Panels may only be cut, drilled or modified to effect a temporary repair during a race. Prior to the next race the repaired panel(s) must be brought back to conformity of these regulations.

5.7 ENGINE

5.7.1 General Engine Regulations

The engine must be a standard 3 cylinder Citroen, Peugeot or Toyota unit, engine type code 1KR-FE, not exceeding 998cc. No engine modifications are allowed whatsoever. The fitting of standard pattern parts is not allowed unless expressly allowed in the following regulations.

5.7.2 Camshaft

No modifications to the standard camshaft are allowed whatsoever.

5.7.3 Crankshaft

No modifications to the standard crankshaft are allowed whatsoever.

5.7.4 Flywheel

No modifications to the standard flywheel are allowed whatsoever.

5.7.5 Clutch

The standard or standard pattern Citroen clutch and pressure plate must be used.

5.7.6 Cylinder Dimensions

No modifications to the standard cylinder block are allowed whatsoever.

5.7.7 Cylinder Heads

No modifications to the standard cylinder heads are allowed whatsoever.

5.7.8 Valve Gear

No modifications to the standard valve gear are allowed whatsoever.

5.7.9 Pistons

No modifications to the standard pistons are allowed whatsoever.

5.7.10 Lubrication System

No modifications to the standard lubrication system are allowed whatsoever.

5.7.11 **Engine Inspection Seal**

Should it be necessary for an engine to be inspected, 2 bolts at the front of the sump and 2 bolts at the front of the rocker cover will be replaced by club supplied drilled bolts. The 2 sump bolts will be wired together and sealed by the Eligibility Scrutineer. The 2 rocker cover bolts will be wired together and sealed by the Eligibility Scrutineer. The engine will be made available for inspection as prescribed by Motorsport UK General Regulations.

The following photographs show the location of the sump and rocker cover bolts.



5.7.11.1 Inspection of the sealed engine will be made by comparison to a standard OEM engine and / or standard OEM parts. Should any component (5.4.1.3) of the sealed engine be in non-compliance with that of the standard example engine or part then the competitor may be reported to the Clerk of the Course for further action. (5.2.2).

5.7.12 **Air Conditioning**

If fitted as standard the air conditioning compressor and associated pipework may be removed.

5.7.13 **Location**

The engine must be located in the manufacturer's original position by the manufacturer's intended method.

5.7.14 **Cooling Systems**

5.7.14.1 No modifications to the standard cooling system are allowed whatsoever.

5.7.14.2 The water pump must be the OEM part, must not be modified in any way and the impellor must be present and working as the manufacturer intended.

5.7.14.3 The auxiliary belt must have all 6 ribs present. Only the following part numbers from the specified suppliers may be used:

Citroen
5750 QJ
5750 QK

EuroCarParts
202772925

GSF
134RE0600

Andrew Page
6PK853

5.7.15 **Induction Systems**

No modifications to the standard induction system are allowed whatsoever. This includes that the use of standard or standard pattern air filters is mandatory. The use of free flow type filters is not permitted. Other than cars adapted for disabled drivers using the OEM Automatic actuation system, 'Fly by Wire' throttle bodies are not permitted.

5.7.16 **Exhaust Systems**

5.7.16.1 No modifications to the standard exhaust system are allowed except as specified in 5.7.16. Removal, repositioning or modification of the Catalytic converter is not permitted.

5.7.16.2 A slip joint may be fitted to the horizontal section of the front exhaust pipe to enable the engine to be removed without needing to remove the whole exhaust pipe and fuel tank guard. The exhaust pipe must be cut 150mm forwards from the exhaust hanger bracket as shown below;



The overall length of the exhaust centre pipe must not be altered. You may either use a Universal Exhaust Pipe Sleeve Clamp as shown below or make a slip joint.



Universal Exhaust Pipe Sleeve Clamp

If using a Sleeve Clamp it must be no more than 100mm long and the correct diameter for the exhaust pipe to ensure a complete seal.

If using a slip joint, the outer tube of the slip joint must be no longer than 100mm. The internal diameter must be a snug fit over the exhaust pipe and it must be welded completely around its circumference to the rear section of the exhaust pipe. The sliding portion of the joint must be 50mm long.

5.7.16.3 The hanger bar on the rear silencer box may be repaired.

5.7.16.4 Only the following part numbers from the specified suppliers may be used:

Part	Citroen	EuroCarParts	GSF	Andrew Page
Catalytic Converter	0342 L5 or 0342 K8	724540520	215PC1489	BM91263H
Centre pipe	1717 CY	706540181	220PC0050	CN548K
Rear silencer	1730 JF or 1730 HO	705730271	252PC0099	CN549J

5.7.17 Ignition Systems

5.7.17.1 No modifications or additions to the standard ignition system are allowed whatsoever. The electrical and physical attributes of the Engine Management Systems (ECU) must be totally standard; except that the C1 Racing Club Map may be installed and used on the ECU. The Championship Organisers reserve the right to download data from a competitors ECU and to upload C1 Racing Club data to the ECU. The Championship Organisers reserve the right to require competitors to submit their ECUs for compliance checking at any time.

5.7.17.2 It is mandatory to use spark plugs with the following part numbers; Denso K20HR-U11, NGK LFR6C-11, Bosch FR8 SC+ or Bosch FR7 SE.

5.7.18 Fuel Delivery Systems

5.7.18.1 The manufacturer's entire fuel delivery system must be retained unmodified.

5.7.18.2 The use of alternative fuel pumps or pressure regulation equipment is prohibited.

5.7.19 Prohibited Modifications

With the exception of the items detailed it is expressly forbidden to machine, mill, grind, polish, weld, modify or otherwise adapt parts in any way whatsoever.

5.8 SUSPENSIONS

5.8.1 Permitted Modifications

5.8.1.1 Only the following damper part numbers from the specified suppliers may be used.

Part	Citroen	KYB
Front left strut	5202 SA	332808
Front right strut	5202 SC	332807
Rear damper	5206 EG	343808

5.8.1.2 No modifications to dampers are allowed. Bump stop rubbers must be standard OEM type. The use of more than one bump stop per damper is not permitted. Only bump stops intended by the manufacturer for fitment to the front of the car may be fitted to the front of the car. Only bump stops intended by the manufacturer for fitment to the rear of the car may be fitted to the rear of the car.

- 5.8.1.3 The only spring allowed is the Apex 70-4200. Rear springs must be fitted in the correct orientation (closed coils to the bodyshell) and fitted with standard OEM rubber seats.
- 5.8.1.4 Upper and/or lower front strut braces are permitted, provided that they are bolt-in items that require no modifications to the bodyshell for fitment and that they are firmly attached to the bodyshell at both ends.
- 5.8.1.5 The C1 Racing Club supplied lower front wishbones may be used together with the C1 Racing Club extended driveshafts and track rod extenders. The standard front wishbone rear bush may be replaced with Powerflex Polybush part no: PFF12/702. It is permitted to 'tack' weld the outer casing of the Polybush to the wishbone.
- 5.8.1.6 Rear wheel geometry may be adjusted by the use of shims fitted between the rear suspension cross member and the wheel bearing hub assembly. Standard bolts must be used and one bolt position must have no shims. The maximum camber allowed is -3.5°.
- 5.8.1.7 Front wheel camber must not exceed -4.0°.
- 5.8.1.8 Anti-roll bar drop links may be replaced by Honda Civic drop link rods with part number 90112SE0000.
- 5.8.1.9 No other modifications are allowed.

5.8.2 Prohibited Modifications

- 5.8.2.1 No modifications to the suspension, mounting points, rubber bushes, shock absorbers, springs or wheel alignment geometry are allowed other than from the consequences of changes by those specified in 5.8.1.1 to 5.8.1.9.

5.9 TRANSMISSIONS

- 5.9.1 The transmission must be the standard OEM fitment with type code C550 or C553. It must be housed (in the case of clutch and gear train) within the standard alloy OEM gearbox housing/bell housing and mounted in the manufacturer's intended position.
- 5.9.2 One of the following standard Citroen C1 gearboxes must be used without modification of any kind

	C550 (2005 - Sept2010)	C553 (Sept2010 - May2014)
First	3.545	3.545
Second	1.913	1.913
Third	1.310	1.161
Fourth	1.027	0.973

Fifth	0.850	0.804
Diff	3.550	3.550

- 5.9.2.1 The 3.550 final drive must be used, no other final drive is permitted.
- 5.9.3 The use of any Limited Slip Differential or any device which provides similar influence upon the front wheels is not permitted.
- 5.9.4 **Permitted Modifications**
- 5.9.4.1 The C1 Racing Club supplied extended drive shafts must be used when the C1 Racing Club supplied wishbones are fitted.
- 5.9.4.2 You may use any of the permitted gearboxes in any of the permitted cars.
- 5.9.4.3 The OEM Automatic actuation system is permitted with no modifications whatsoever.
- 5.9.5 No other modifications or changes are allowed to the transmission assemblies or components.
- 5.10 ELECTRICS**
- 5.10.1 **General**
The standard C1 electrical system must be retained. It is not permissible to modify the wiring loom or its ancillaries except for the following:
- Air bag firing mechanism must be removed.
 - Wires for the additional optional front spot lights as defined in 5.10.2.3.
 - Wires for optional identification lights as defined in 5.10.2.4.
 - Modification to reverse light wiring to convert to rain light as defined in 5.10.3.
 - The fitment of a Master Switch circuit breaker as defined in 5.10.7.
 - Modification to ignition switch as defined in 5.10.8
- 5.10.1.1 Power for cameras must be taken from the cigarette lighter socket or from the power feed described in 5.10.1.2. It is permissible to fit a cigarette lighter socket multi way adaptor.
- 5.10.1.2 The positive feed to the transponder should be taken from the blue wire on the back of the ignition switch multi cable connector
- 5.10.1.3 Nothing may be plugged into the OBD port unless directed by the Championship Organiser. The OBD port must be permanently connected to the car's electronic systems as the manufacturer intended. No modifications are allowed to the OBD connector or the wiring to it.
- 5.10.2 **Exterior Lighting**
- 5.10.2.1 All standard lights (front and rear side lights, 3 brake lights, front and rear indicators, dip and main beam headlights, rain lights) must all be present and working.

- 5.10.2.2 Standard or standard pattern light units must be used. HID, LED and upgraded H4 bulbs are permitted.
- 5.10.2.3 One pair of C1 Racing Club supplied or Masai (SKU 8-REC-4-LED-40W-Com-6012) LED spot lights may be fitted directly to the unmodified fitting bracket supplied by The C1 Racing Club. The spot lights will be fed from a fused relay that is operated by an input from the main beam light wires behind the left-hand side headlight unit. The spot lights will activate at the same time as the standard main beam bulbs and no additional or independent operation is permitted. Additional internal switches are not allowed.
- 5.10.2.4 Identification lights are permitted. Power must be supplied by the side light circuit. The identification lights will activate at the same time as the standard side lights and no additional or independent operation is permitted. Additional internal switches are not allowed.
- 5.10.2.5 All lights detailed in Regulation 5.10.2.1 must be in working order throughout the entire Event.
- 5.10.3 **Rain Light**
- 5.10.3.1 The reversing light must be converted to a red bulb and illuminate simultaneously with the rear fog light to act as an Motorsport UK compliant rain light as defined in K.5.1. No additional rain lights are permitted.
- 5.10.3.2 Additional wiring may be fitted to link the rear fog light to the reversing light or the links in the reversing light fitting may be altered so the reversing light is illuminated when the rear fog light circuit is active.
- 5.10.4 **Batteries**
- 5.10.4.1 The 12 volt battery must be equivalent in size, weight and amp hours as the original manufacturer's battery, fitted in the standard position and must be firmly secured.
- 5.10.5 **Alternator / Charging Circuit**
- 5.10.5.1 A functioning standard OEM specification alternator must be fitted. No modifications are allowed to the alternator, its drive mechanism or electrical circuits.
- 5.10.5.2 The auxiliary belt must have sufficient tension to make the alternator function as intended by the manufacturer.
- 5.10.5.3 The Charging Circuit must be connected and operational all times whilst the Engine is running.
- 5.10.6 **Windscreen Wipers**
- 5.10.6.1 Standard or standard pattern front and rear windscreen wipers and washers must be fitted and fully operational. The front wiper blade must be at least 650mm long. No modifications are allowed to the windscreen wiper blade, windscreen wiper mechanism or windscreen washer system.

5.10.7 **Master Switch**

- 5.10.7.1 Should a solid-state master switch battery isolator not be fitted; a cable operated master switch battery isolator shall be mounted on the centre console within the confines of 2 vertical planes which are defined by the external faces of the centre console and a horizontal plane at the level of the bottom of the heater controls. A rearward extension to the mounting position is permitted to enable operation of the master switch with the driver seated in the full racing position with seat belts firmly secured.
- 5.10.7.2 One side of the secondary switch labelled Z or 2 on the back of the master cut-out switch must be introduced into the blue wire from the ignition switch multi cable connector.
- 5.10.7.3 Should a solid-state master switch battery isolator is installed, the internal operating button shall be mounted on the centre console within the confines of 2 vertical planes which are defined by the external faces of the centre console and a horizontal plane at the level of the bottom of the heater controls. A rearward extension to the mounting position is permitted to enable operation of the master switch with the driver seated in the full racing position with seat belts firmly secured.

5.10.8 **Ignition Switch**

- 5.10.8.1 It is permitted to modify the ignition switch so that the steering lock is disabled.

5.11 **BRAKES**

- 5.11.1 Mintex MDB2743-1144 brake pads must be used, supplied by Wheels Around.
- 5.11.2 The ABS system must be operational at all times. Permanent or temporary disabling of the ABS system is prohibited.
- 5.11.3 Standard or standard pattern brake discs must be used. Brake discs with any friction surface grooves, holes, slots or other performance enhancing features are prohibited.
- 5.11.4 It is not permissible to modify the brake pipes. Standard rubber brake hoses may be replaced by braided hoses.
- 5.11.5 The standard handbrake must remain in the manufacturers intended position and be fully operational.

5.12 **WHEELS/STEERING**

- 5.12.1 Other than the extended track rod kit available from The C1 Racing Club no modifications of any kind are allowed to the steering system.
- 5.12.2 The standard steering wheel may be used. A Motorsport UK approved alternative steering wheel and either quick release or fixed boss is permitted.

- 5.12.3 The standard horn must be fitted, working and operated from the steering wheel centre.
- 5.12.4 The passenger airbag must be completely removed, the steering wheel air bag will be completely removed when fitting an alternative steering wheel but when retaining the standard steering wheel the explosive charge must be removed to completely disable the airbag but retain the function of the horn operation.
- 5.12.5 Wheel spacers are not permitted.
- 5.12.6 Standard wheel bolts must be used, wheel studs are not permitted.
- 5.12.7 Original Equipment Citroen 4.5J x 14ET39 steel wheels or The C1 Racing Club alloy wheels, part number 9607W4, must be used.

5.13 TYRES

5.13.1 Specifications

- 5.13.1.1 The permitted size is 155-55 X 14.
- 5.13.1.2 The use of tyre heating/heat retention devices, tyre treatments and compounds is prohibited.
- 5.13.1.3 The tyres used on the front axle during qualifying or racing must not be buffed, cut, shaved, planed or mechanically interfered with in any way.
- 5.13.1.4 Tyres must have not less than 1.6mm of tread remaining at the start of an event. (Motorsport UK General Regulation J.5.9.2).

5.13.2 Nominated Manufacturer

- 5.13.2.1 All tyres used during an event must be Nankang AS1.

5.14 WEIGHT

- 5.14.1 Cars must have a minimum weight of 910kg at all times during competition, to include the driver in full racing kit seated in the normal driving position.
- 5.14.2 Any ballast fitted must comply with Motorsport UK General Regulation J.5.15.2 to J.5.15.4 and must not exceed 50kg, and a maximum of 25kg in any one location.

5.15 FUEL TANK/FUEL

5.15.1 Fuel Tank

- 5.15.1.1 The fuel tank must be a Citroen C1 standard production item fitted in the manufacturer's original position.
- 5.15.1.2 Modifications to the fuel tank, sender unit, fuel pump and pressure regulator are not permitted.

5.15.1.3 The fuel pump cover panel must allow access to the fuel pump and pressure regulator. The cover panel may have mechanical fasteners fitted to enable access to the fuel pump and pressure regulator.

5.15.2 **Filler Cap**

5.15.2.1 A filler cap must be fitted that complies with Section K14.1.2 of the Motorsport UK Yearbook. The standard lockable filler cap may be replaced by a non-lockable one.

5.15.3 **Tank Guard**

5.15.3.1 A fuel tank guard supplied by The C1 Racing Club must be fitted in the location specified.

5.15.4 **Fuel**

5.15.4.1 Only petrol as defined in Section B Nomenclature & Definitions, Pump Fuel a) section of the Motorsport UK Yearbook and complying with BSEN228 may be used; fuel which exceeds the stated RON (max) levels in Appendix 1 of Section B Nomenclature & Definitions is prohibited even if it is sold/promoted as being legal for UK Competition and/or obtainable from 'roadside' pumps.

5.15.4.2 Additives are not permitted.

5.15.4.3 The introduction of any other media into the engine is prohibited.

5.15.4.4 In all cases an audit trail for all fuel purchased must be demonstrable.

5.16 **SILENCING**

Vehicles must be silenced in accordance with Motorsport UK Regulation [J 5.17] & [J 5.18].